









Product Family











AIRVISOR 2

AIRVISOR 2 kits are constant flow supplied air respirators designed to EN14594, to be used in conjunction with a filter system like the Honeywell Clearflow 3. A regulator in the waistbelt unit maintains an over-pressure inside the visor ensuring that no contamination can enter.

Honeywell

Product Numbers & Ordering Information

	Product Numbers	Details
	1013938	Airvisor 2 MV Std Paint kit Full kit : AIRVISOR 2 MV with acetate chemical resistant visor, spraygun air hose with quick release connectors, 2 disposable visor covers, fabric hood and neck cover, waistbelt complete, carry bag. For painting applications.
	1013939	Airvisor 2 MV Std Chemical kit Full kit : AIRVISOR 2 MV with acetate chemical resistant visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For chemical applications.
	1013980	Airvisor 2 MV Std Industry kit Full kit : AIRVISOR 2 MV with impact resistant polycarbonate visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For industrial applications.
	1013932	Airvisor 2 Paint Spraying Kit Full kit : AIRVISOR 2 standard with acetate chemical resistant visor, spraygun air hose with quick release connectors, 2 disposable visor covers, fabric hood and neck cover, waistbelt complete, carry bag. For painting applications.
	1013934	Airvisor 2 Chemical Kit Full kit : AIRVISOR 2 standard with acetate chemical resistant visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For chemical applications.
	1013935	Airvisor 2 Industrial Kit Full kit : AIRVISOR 2 standard with impact resistant polycarbonate visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For industrial applications.

	1013983	Airvisor 2 FV-Series Welding Kit Full kit : AIRVISOR 2 MV with high temperature welding shell, viewing window (size 90mm X 110mm), impact resistant polycarbonate inner visor, one flame retardant fabric cassette, one flame retardant head cover, air supply tube and diffuser, waistbelt with carbon cartridge and regulator, carrying bag. Welding glass not included - For welding applications.
	1013987	Airvisor 2 W-Series Welding Kit Full kit : AIRVISOR 2 standard with high temperature welding shell, viewing window (size 90mm X 110mm), impact resistant polycarbonate inner visor, one flame retardant fabric cassette, one flame retardant head cover, air supply tube and diffuser, waistbelt with carbon cartridge and regulator, carrying bag. Welding glass not included - For welding applications.
	1765058	Airvisor 2 DAC Paint Spraying Kit double action connector Full kit : AIRVISOR 2 MV with acetate chemical resistant visor, spraygun air hose with quick release connectors, 2 disposable visor covers, fabric hood and neck cover, waistbelt complete, carry bag. For painting applications.
	1765059	Airvisor 2 DAC Chemical Kit double action connector Full kit : AIRVISOR 2 MV with acetate chemical resistant visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For chemical applications.
	1765060	Airvisor 2 DAC Industrial Kit double action connector Full kit : AIRVISOR 2 MV with impact resistant polycarbonate visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For industrial applications.
	1765061	Airvisor 2 MV DAC Paint Spraying Kit double action connector Full kit : AIRVISOR 2 standard with double action coupling and acetate chemical resistant visor, spraygun air hose with quick release connectors, 2 disposable visor covers, fabric hood and neck cover, waistbelt complete, carry bag. For painting applications.
	1765062	Airvisor 2 MV DAC Chemical Kit double action connector Full kit : AIRVISOR 2 standard with double action coupling and acetate chemical resistant visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For chemical applications.
	1765063	Airvisor 2 MV DAC Industrial Kit double action connector Full kit : AIRVISOR 2 standard with double action coupling and impact resistant polycarbonate visor, 2 disposable visor covers and head cover, waistbelt complete, carrying bag. For industrial applications.
	1765064	Airvisor 2 FV-Series DAC Welding Kit double action connector Full kit : AIRVISOR 2 MV with high temperature welding shell, viewing window (size 90mm X 110mm), impact resistant polycarbonate inner visor, double action connector, one flame retardant fabric cassette, one flame retardant head cover, air supply tube and diffuser, waistbelt with carbon cartridge and regulator, carrying bag. Welding glass not included - For welding applications.
	1765065	Airvisor 2 W-Series DAC Welding Kit double action connector Full kit : AIRVISOR 2 standard with high temperature welding shell, viewing window (size 90mm X 110mm), impact resistant polycarbonate inner visor, double action connector, one flame retardant fabric cassette, one flame retardant head cover, air supply tube and diffuser, waistbelt with carbon cartridge and regulator, carrying bag. Welding glass not included - For welding applications.

Overview

Key Features

AIRVISOR 2

Two types of visor: Acetate visor provides resistance against solvents. Polycarbonate visor available for areas where impact is the main risk.

Fabric head and neck cover

Quick connect air supply hose

Warning whistle : operates when the supply pressure is insufficient to guarantee the user's safety

Quick release connector and spraygun air hose, as delivered in the Paint Spraying kit

Inlet connector for air from the factory compressed air system – always use a compressed air supply hose designed by Honeywell Safety Products.

Also available in a design supporting the use of double action connectors.

Recommended Industries/Use

- Chemical
- Construction
- Food Services
- Manufacturing
- Municipal Services
- Pharmaceutical
- Transportation

Hazards

- Airborne Particulates

Regulations

- EN14594 - Respiratory protective devices - Continuous flow compressed air line breathing apparatus
- EN166 - Personal eye-protection - Specifications

Historical Brand

Wilson

Specifications

Maximum flow rate

- 290 l/min

Operating air pressure

- 4,2 bars (58 psi) to 7 bars (102 psi)

Maximum operating temperature

- 35°C

Literature & Documents

Airvisor 2 user manual - Multi languages

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/SAR/4294982125/1033.aspx

Training & Proper Use

Refer to user manual