



PROFESSIONAL

## GOLF 275 TWIN



Lifejacket level 275



# GOLF 275 TWIN

Universal SOLAS lifejacket with a patented twin chamber buoyancy chamber offering redundant safety to the latest SOLAS specification by the IMO.

The upper compartment of this twin chamber lifejacket features a fully automatic CO<sub>2</sub> firing mechanism to provide buoyancy of 275 Newton. However in the very rare event of unforeseen damage or gas leakage, the reserve compartment can be deployed via a manually operated CO<sub>2</sub> cylinder to pro-

vide full replacement buoyancy. Available in harness and non-harness versions. Options include different outer covers as well accessories such as spray hood and emergency PLB.



# SPECIFICATION

General technical data	
Type:	GOLF 275 TWIN
Part No.:	14256, 14164 (with safety harness)
Approval:	EN ISO 12402-2 SOLAS 74 (MSC.200(80)) EN ISO 12401 (only lifejacket with safety harness)
Buoyancy:	approx. 280 N
Colour:	Dark blue
Weight:	approx. 1.9 kg
CO <sub>2</sub> -Cartridge:	60 g CO <sub>2</sub> -Cartridge
Size:	50 kg and more body weight up to 175 cm chest measurement
Temperature range:	Storage: -54 °C to +70 °C Operation: -10 °C to +70 °C
Geographical range:	unlimited*
Application:	For all industrial and commercial inshore or offshore uses.
* to protect the SECUMAR Pill/Pill-Box against premature disintegration caused by high atmospheric humidity/temperature SECUMAR highly recommends to adapt the changing interval to these specific areas. The standard interval should be shortened to an appropriate period.	

Protective Stole			
Integrated Safety Harness acc. to EN ISO 12401:	- / • (only lifejacket with safety harness)	Colour:	Dark blue
Material:	Polyamide fabric	Closed with:	Zip fastener with predetermined breaking point
Adjustment waist belt:	1 lateral slider	Buckle:	SECUMAR Click-Buckle, 50 mm
Lifting becket (3,2 kN):	•	Back strap:	Single
Window:	-	Pocket for accessories:	-
Service-Zipper:	-	Pocket for nametag:	-
Characteristics: With the patented SECUMAR CLICK-buckle the donning and doffing of the lifejacket is very easy, it is donned like a normal jacket.			

Buoyancy chamber			
Design:	Buoyancy chamber with twin chamber membrane technology	Colour:	Yellow
Oral valve:	•	Retro reflecting tape:	400 cm <sup>2</sup> (Material: 3M®)
Material:	Polyurethane-coated polyamide fabric	Overpressure valve:	•
Pocket for transmitter:	-		
Characteristics: The buoyancy chamber is separated with an internal membrane to an upper and lower compartment. The upper compartment is the standard chamber and will be inflated automatically upon contact with water.			

- Standard/◦ Optional/- Not available

### Inflation device

	1. Chamber	2. Chamber
Operation:	Automatic activation upon the SECUMAR Pill contact with water.	Manual activation with rip cord.
Type:	SECUMATIC 3001S	SECU 301SM
Indicator:	3 Indicators	2 Indicators
Characteristics:	Torque safe tying system (Positorque®) prevents from unintended loosening of the CO <sub>2</sub> -cartridge by means of vibration and shock. Three indicators offer an easy possibility of control and inspection before every use: SECUMAR Pill is inserted, CO <sub>2</sub> -cartridge is fitted correctly and activation lever is secured.	Torque safe tying system (Positorque®) prevents from unintended loosening of the CO <sub>2</sub> -cartridge by means of vibration and shock. Two indicators offer an easy possibility of control and inspection before every use: CO <sub>2</sub> -cartridge is fitted correctly and activation lever is secured.

### Equipment

Sprayhood:	o	Crutch strap:	o
Distress light:	SECULUX CFX-II	CO <sub>2</sub> -Cartridge:	2x 60 g CO <sub>2</sub> -Cartridge
Neck fleece:	–	Buddy Line:	•
Transmitter:	–	Signal whistle:	•
Lifeline:	o	Instructions, multi-language:	•
Characteristics: The service label on the waist belt shows you at a glance when your lifejacket should be serviced again by the SECUMAR service.			

### Model variants

			
Golf 275 Twin Cordura (P/N: 14258) Golf 275 Twin Cordura PLB (P/N: 14264)	Golf 275 Twin SPR (P/N: 14260) Golf 275 Twin SPR Harness (P/N: 14251)	Golf 275 Twin PLB (P/N: 14262) Golf 275 Twin SPR PLB (P/N: 14266)	Golf 275 Twin SPR PLB for Sea Marshall AU9 and AU10 (P/N: 14796)

### Optional Equipment/ Spare parts

			
60 g CO <sub>2</sub> -Cartridge AUTO (P/N: 11896) 60 g CO <sub>2</sub> -Cartridge HAND (P/N: 11897)	Distress light SECULUX CFX-II (P/N: 12947)	Lifeline 2040LL (P/N: 421) Lifeline X-treme (P/N: 12207)	Spraycap (P/N: 14291) Spraycap (with PLB; P/N: 14561)

• Standard/o Optional/– Not available

09/2015



CE: PPE in conformance with Directive 89/686/EWG, type-approved to EN standards and/or DIN EN ISO 12402



CE-Wheel mark: PPE in conformance with MED Marine Equipment Directive 96/98/EG and approved to SOLAS/IMO regulations for marine rescue equipment.



SECUMAR is a member of the Emergency Sea Rescue Equipment Trade Federation (FSR), a union of suppliers and importers of all water rescue equipment. For further information, see [www.fsr.de](http://www.fsr.de).



Bernhardt Apparatebau GmbH u. Co.  
Lifesaving Equipment for Sea and Air  
PO Box 1190 · 25487 Holm, Germany  
Tel.: +49 4103 125 – 0  
Fax: +49 4103 125 – 100  
[www.secumar.com](http://www.secumar.com)

